

VARITECH



- Load capacity: 499 kg (1,100 lbs)
- Bed weight: 140.5 kg (309 lbs)
- Minimum height: 33.3 cm (13 1/8 in.) Maximum height: 76.8 cm (30 1/4 in.)
- Maximum backrest angle: 68 degrees Maximum footrest angle: 34 degrees
- Bedspring dimensions: 88.9 cm (35 in.) to 134.6 cm (53 in.) x 198.1 cm (78 in.)
- Overall external dimensions (with sides, half-section): 102.5 cm (41 in.) to 149.9 cm (59 in.) x 229.6 cm (90 3/8 in.)
- Recommended mattress height: 12.7 cm (5 in.)
- Support for trapeze bar included
- Trendelenburg position included

FEATURES

- Whisper-quiet direct-current linear motor
- IP54-approved electrical components protected from dust and water infiltration
- 6 receptacles for IV holder stems
- Battery ensuring temporary autonomous operation
- Casters equipped with a central brake system (synchronized) (2 x 2 casters)
- Possibility of moving the bed even when in its lowest height position
- Metal surfaces covered with electrostatic powder paint
- Selectable, manually adjustable foot angle (choice of three positions: flexion, standard and extension)
- Bed may be separated into two sections for easier transport
- Adjustable-width bedspring
- Headboard and footboard bumpers
- Afforable ajustable-width bariatric bed
- Bed with the highest load capacity in its category
- Authentic Canadian product

OPTIONS

- Rotating half-length bed sides
- Cast composite or melamine headboard and footboard
- Trapeze bar (which follows the bed motions when adjusting in height)
- Nurse control
- Built-in digital scale
- Sectional Varitech SHD mattress
- Transportation dolly

APPROVALS

- CSA Canada & USA - File No. 1608300

Standards: C22.2 No. 0M91

C22.2 No. 601.1 Amendment 2 C22.2 No. 60601-2-38-03

C22.2 No. 601.1 M90 UL No. 60601-1

C22.2 No. 601.1S1 94

Rotec International holds medical instrument manufacturing licenses issued by Health Canada and the FDA.
Photos and specifications may change without prior notice.