

Q6 EDGE[®] 2 & Q6 EDGE[®] Z & Q6 EDGE[®] HD COLOR OPTIONS



Q6 EDGE[®] COLOR OPTIONS



Q6 SERIES

THE POWER YOU TRUST



Beamsville, Ontario ▪ 888-570-1113 ▪ Visit us on the web: www.quantumrehab.com

The information contained herein is correct at the time of publication. We reserve the right to alter specifications without prior notice. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.





Q6 EDGE® 2.0

With features like standard 6 mph motors and advanced responsiveness, the Q6 Edge® 2.0 is engineered to meet the performance needs of the most active user. The Q6 Edge 2.0 accepts a complete range of seating and electronics options to deliver exceptional rehab capability at an excellent value, and is available with our iLevel® technology.

With iLevel® option...

- Up to 10" of seat elevation (in 16 seconds) at walking speed (up to 3.5 mph)




Q6 EDGE® HD

With features like standard 4-pole motors, Mid-Wheel 6° Drive Design and ATX Suspension, the Q6 Edge® HD is engineered to meet the performance needs of the most active user. The Q6 Edge HD accepts a complete range of seating and electronics options and offers an increased weight capacity of 450 lbs. to deliver exceptional rehab capability at an excellent value. It is also available with our iLevel® technology (400 lbs. weight capacity).

With iLevel® option...

- Up to 10" of seat elevation (in 24 seconds) at walking speed (up to 3.5 mph)



Q6 EDGE®

With features like standard 4-pole motors, Mid-Wheel 6° Drive Design and ATX Suspension, the Q6 Edge® is engineered to meet the performance needs of the most active user. The Q6 Edge accepts a complete range of seating and electronics options to deliver exceptional rehab capability at an excellent value.

Also Available...

- Q6 Edge® with 6 mph high-speed motor package




Q6 EDGE® Z

The Q6 Edge® Z utilizes powerful 4-pole motors for maximum torque and Mid-Wheel 6° design for aggressive outdoor performance and precision indoor maneuverability. The Q6 Edge Z accepts a broad range of exclusive seating and electronics options for unmatched adaptability and rehab capability, and is available with our iLevel® technology.

With iLevel® option...

- Up to 10" of seat elevation (in 16 seconds) at walking speed (up to 3.5 mph)



	Q6 EDGE® 2.0	Q6 EDGE®	Q6 EDGE® HD	Q6 EDGE® Z
Drive Wheels	14" solid or pneumatic ²	14" solid or pneumatic ²	14" solid or pneumatic ²	14" solid or pneumatic ²
OMNI-Casters	Front: 6" solid (Optional: 8" Solid) Rear: 6" solid (Optional: 8" Solid)	Front: 6" solid Rear: 6" solid	Front: 6" solid Rear: 6" solid	Front: 6" solid Rear: 6" solid
Suspension	Active-Trac® ATX with enhanced rear suspension	Active-Trac® ATX with enhanced rear suspension	Active-Trac® ATX with integrated rear dual-strut suspension and articulating caster beam	Active-Trac® ATX with enhanced rear suspension
Maximum Speed ¹	Up to 6 mph	Up to 5 mph / Up to 6 mph ^{2,3}	Up to 4.7 mph	Up to 6 mph / 8 mph ^{2,3}
Ground Clearance	2.7" (at battery tray)	3" at frame center	3" at frame center	3" (at frame base)
Turning Radius ⁴	20.5" (6" casters); 23.25" (8" casters)	20"	19.75"	19.75"
Overall Size	Length: 43.5" (6" casters); 40.48" (8" casters) Width: 24.4"	Length: 35.5" Width: 24"	Length: 35.6" (base only) Width: 26.25" (base only)	Length: 35.6" Width: 26.25"
SEATING SIZES	TRU-Balance® 2			
Synergy®/Static	N/A	W: 10"-22" D: 10"-22"	W: 20"-28" D: 20"-28"	N/A
Power Tilt	N/A	W: 14"-22" D: 14"-22"	W: 20"-28" D: 20"-28"	N/A
Lift & Tilt	N/A	N/A	N/A	N/A
Pediatric Tilt	N/A	W: 11"-14" D: 10"-18"	N/A	N/A
SEATING SIZES	TRU-Balance® 3			
Static	W: 10"-22" D: 10"-22"	W: 10"-22" D: 10"-22"	W: 20"-32" D: 20"-28"	W: 10"-24" D: 10"-24"
Power Tilt	W: 12"-22" D: 12"-22"	W: 12"-22" D: 12"-22"	W: 20"-32" D: 20"-25"	W: 12"-24" D: 14"-24"
Lift & Tilt	W: 16"-22" D: 14"-22"	W: 12"-22" D: 12"-22"	W: 20"-24" D: 20"-25"	W: 12"-24" D: 14"-24"
Pediatric Tilt	N/A	N/A	N/A	N/A
SEAT-TO-FLOOR HEIGHTS	TRU-Balance® 2			
Synergy®/Static ^{5,6}	N/A	15.9"-17.9"	16.5"-18.5"	N/A
Power Tilt ^{5,6}	N/A	17.3"-19.3"	18.2"-20.9"	N/A
Lift & Tilt ^{5,6}	N/A	N/A	N/A	N/A
Pediatric Tilt ^{5,6}	N/A	17.25"-19.25"	N/A	N/A
SEAT-TO-FLOOR HEIGHTS	TRU-Balance® 3			
Static ^{5,6}	16.5"-18.5"	16.5"-18.5"	16.5"-18.5"	16.5"-18.5"
Power Tilt ^{5,6}	17.5"-19.5"	17.5"-19.5"	18.5"-20.5"	18.5"-20.5"
Lift & Tilt ^{5,6}	17.5"-19.5"	18"-20"	18.5"-20.5"	18.5"-20.5"
Pediatric Tilt ^{5,6}	N/A	N/A	N/A	N/A
Drivetrain	2-motor, Mid-Wheel 6°	2-motor, Mid-Wheel 6°	2-motor, Mid-Wheel 6°	2-motor, Mid-Wheel 6°
Batteries	Two 12 volt, deep cycle NF-22	Two 12 volt, deep cycle NF-22	Two 12 volt, deep cycle Group 24	Two 12 volt Group 24
Range per Charge ^{1,10}	Up to 16.19 miles	Up to 15.5 miles	Up to 16.7 miles	Up to 16.94 miles
Battery Charger	8A, off-board	8A, off-board	8A, off-board	8A, off-board
Available Electronics	Q-Logic 2 NE Q-Logic 2 NE+ Q-Logic 3 EX	Q-Logic 2 NE Q-Logic 2 NE+ Q-Logic 2 EX	Q-Logic 2 NE Q-Logic 2 NE+ Q-Logic 2 EX	Q-Logic 2 NE Q-Logic 2 NE+ Q-Logic 2 EX ⁸
Weight Capacity	300 lbs. (user weight)	300 lbs. (user weight)	450 lbs. (user weight) ⁷	300 lbs. (user weight)
Base Weight	138.6 lbs. (6" casters) 148 lbs. (8" casters)	138 lbs.	143.5 lbs.	143.5 lbs.
Battery Weight ⁹	38 lbs. (each)	38 lbs. (each)	52 lbs. (each)	52 lbs. (each)
Warranty	Lifetime limited warranty on frame; 2-year warranty on electronics and drive motor	Lifetime limited warranty on frame; 2-year warranty on electronics and drive motor	Lifetime limited warranty on frame; 2-year warranty on electronics and drive motor	Lifetime limited warranty on frame; 2-year warranty on electronics and drive motor

FOOTNOTES:

- Range and speed vary with user weight, terrain type, battery charge, battery condition and tire pressure.
- Optional.
- High-speed motor option will reduce range.
- Without front riggings.
- All measurements +/- 1/8" with 18" x 18" seat, fixed towers, 300 lbs. weight capacity and solid tires (add 3/8" with pneumatic tires). Widths may increase seat-to-floor height. Contact Customer Service for details. Listed measurements are in the lowest position; does not include elevating system unless specified.
- Power Recline and Power Front Rigging do not increase seat-to-floor height.
- Weight capacity is reduced to 400 lbs. with iLevel® power adjustable seat height.
- Required with high-speed motors.
- Battery weight may vary based on manufacturer.
- Tested in accordance with ANSI/RESNA, WC Vol. 2, Section 4, standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Testing conducted at maximum weight capacities. This specification can be subject to a variance of +10%, -5%.